



**CABLE TIES AND FIXINGS**

## NYLON CABLE TIES

### SPECIFICATION

Kompress Cable Ties are produced to comply with the requirements of Military Specification MIL-S 23190E and supplied in accordance with our ISO 9002 accreditation.

They have a working temperature of -40°C + 85°C and are primarily manufactured from virgin nylon 66 in natural colour, unless specified otherwise, as indicated as below. Kompress Cable Ties are normally supplied in packs of 100 pieces.

### BLACK AND OTHER COLOURS

Most cable ties and accessories are available in black colour. Suffix BL should be added for black products. Many sizes of nylon ties are also available in red, blue, orange, green, yellow, silver grey, purple and other colours. Consult Kompress for details.

e.g. **KCT 100 - 2.5BL**

### BULK PACKS

Most cable ties and accessories widths up to 3.6mm are also available in bulk packs of 1000. If these are required add suffix M.

e.g. **KCT 100 - 2.5M**

### HS UV STABILISED (WEATHER RESISTANT) BLACK

If Cable Ties are to be installed in conditions of high UV radiation, an increased weather resistant version can be obtained. That is achieved by the addition of carbon black stabiliser additive to the Nylon 66 polymer which produces a black UV stabilised product. If this is required add suffix UV to part number. If higher operating temperature is required (110°C) add suffix HSUV.

e.g. **KCT 300 - 4.8UV**

These products are available only in packs of 100 pieces

### HOW TO SPECIFY

The Kompress part numbering system has been carefully devised to help the specifier understand and recognise each element of the code. This simple part numbering system makes specifying easy without constant reference to the catalogue.

This is how the part number is created-

e.g. **KCT 200 - 4.8BLM**

If the variations listed above are required add appropriate suffix.

=

**KCT** (Kompress Cable Tie). **200** (Length mm). **4.8** (Width mm). **BL** (Black Colour). **M** (Bulk Pack).



## STANDARD NYLON 6.6 CABLE TIES



PART NO.	LENGTH mm (inches)	WIDTH mm (inches)	MAX. BUNDLE DIAMETER mm (inches)	MIN. TENSILE STRENGTH Kg (lbs)
<b>TIE WIDTH 2.4 - 2.5mm</b>				
KCT80-2.4	80 (3.15)	2.4 (.094)	17 (.67)	8.0 (17.63)
KCT90-2.4	90 (3.54)	2.4 (.094)	16 (.63)	8.0 (17.63)
KCT100-2.5	100 (3.94)	2.5 (.098)	22 (.87)	8.1 (18)
KCT120-2.5	120 (4.72)	2.5 (.098)	30 (1.18)	8.1 (18)
KCT140-2.5	140 (5.51)	2.5 (.098)	33 (1.3)	8.1 (18)
KCT160-2.5	160 (6.3)	2.5 (.098)	40 (1.57)	8.1 (18)
KCT200-2.5	200 (7.87)	2.5 (.098)	50 (1.97)	8.1 (18)
<b>TIE WIDTH 3.6mm</b>				
KCT120-3.6	121 (4.76)	3.6 (.14)	25 (.98)	18.2 (40)
KCT140-3.6	140 (5.51)	3.6 (.14)	33 (1.3)	18.2 (40)
KCT150-3.6	150 (5.91)	3.6 (.14)	35 (1.38)	18.2 (40)
KCT180-3.6	180 (7.09)	3.6 (.14)	44 (1.73)	18.2 (40)
KCT200-3.6	200 (7.87)	3.6 (.14)	50 (1.97)	18.2 (40)
KCT250-3.6	250 (9.84)	3.6 (.14)	65 (2.56)	18.2 (40)
KCT300-3.6	295 (12)	3.6 (.14)	76 (2.99)	18.2 (40)
KCT370-3.6	370 (14.57)	3.6 (.14)	102 (4.02)	18.2 (40)
<b>TIE WIDTH 4.8mm</b>				
KCT120-4.8	120 (4.72)	4.8 (0.19)	24 (.94)	22.2 (50)
KCT160-4.8	160 (6.3)	4.8 (0.19)	38 (1.5)	22.2 (50)
KCT200-4.8	200 (7.87)	4.8 (0.19)	50 (1.97)	22.2 (50)
KCT250-4.8	250 (9.84)	4.8 (0.19)	60 (2.36)	22.2 (50)
KCT300-4.8	300 (11.81)	4.8 (0.19)	76 (2.99)	22.2 (50)
KCT370-4.8	370 (14.57)	4.8 (0.19)	102 (4.02)	22.2 (50)
KCT450-4.8	450 (17.72)	4.8 (0.19)	116 (4.57)	22.2 (50)
KCT530-4.8	530 (20.87)	4.8 (0.19)	140 (5.51)	22.2 (50)
<b>TIE WIDTH 7.6mm</b>				
KCT150-7.6	150 (5.91)	7.6 (.3)	33 (1.3)	54.4 (120)
KCT200-7.6	200 (7.87)	7.6 (.3)	50 (1.97)	54.4 (120)
KCT250-7.6	250 (9.84)	7.6 (.3)	65 (2.56)	54.4 (120)
KCT300-7.6	292 (11.5)	7.6 (.3)	76 (2.99)	54.4 (120)
KCT370-7.6	368 (14.49)	7.6 (.3)	102 (4.02)	54.4 (120)
<b>TIE WIDTH 9.0mm</b>				
KCT450-9.0	450 (17.72)	9.0 (.35)	127 (5)	79.4 (175)
KCT530-9.0	533m (21)	9.0 (.35)	140 (5.51)	79.4 (175)
KCT650-9.0	650 (25.6)	9.0 (.35)	178 (7)	79.4 (175)
KCT710-9.0	710 (28)	9.0 (.35)	190 (7.48)	79.4 (175)
KCT780-9.0	775 (30.51)	9.0 (.35)	228 (9)	79.4 (175)
KCT830-9.0	812 (32)	9.0 (.35)	239 (9.41)	79.4 (175)
KCT880-9.0	880 (34.64)	9.0 (.35)	254 (10)	79.4 (175)
KCT920-9.0	912 (35.91)	9.0 (.35)	263 (10.35)	79.4 (175)
KCT1000-9.0	1000 (39.37)	9.0 (.35)	305 (12)	79.4 (175)
KCT1220-9.0	1200 (48)	9.0 (.35)	365 (14.37)	79.4 (175)


## ROUND HEAD CABLE TIES



PART NO.	LENGTH mm (inches)	WIDTH mm (inches)	MAX. BUNDLE DIAMETER mm (inches)	MIN. TENSILE STRENGTH Kg (lbs)
<b>TIE WIDTH 2.5mm</b>				
KCTRH100-2.5	100 (3.94)	2.5 (.10)	18 (.71)	10 (22)
KCTRH160-2.5	160 (6.3)	2.5 (.10)	40 (1.57)	10 (22)
KCTRH200-2.5	200 (7.87)	2.5 (.10)	50 (1.97)	10 (22)
<b>TIE WIDTH 2.8mm</b>				
KCTRH250-2.8	250 (9.84)	2.8 (.11)	65 (.71)	10 (22)
<b>TIE WIDTH 3.6mm</b>				
KCTRH140-3.6	140 (5.51)	3.6 (.14)	33 (1.3)	22 (48)
KCTRH200-3.6	200 (7.87)	3.6 (.14)	50 (1.97)	22 (48)
KCTRH300-3.6	295 (12)	3.6 (.14)	76 (3)	22 (48)
KCTRH370-3.6	370 (14.57)	3.6 (.14)	102 (4)	22 (48)
<b>TIE WIDTH 4.8mm</b>				
KCTRH160-4.8	160 (6.3)	4.8 (.19)	38 (1.5)	26 (57)
KCTRH190-4.8	188 (7.4)	4.8 (.19)	43 (1.7)	26 (57)
KCTRH280-4.8	280 (11.02)	4.8 (.19)	70 (2.76)	26 (57)
KCTRH370-4.8	370 (14.57)	4.8 (.19)	102 (4.02)	26 (57)
<b>TIE WIDTH 7.6mm</b>				
KCTRH200-7.6	200 (7.87)	7.6 (.3)	50 (1.97)	65 (143)
KCTRH250-7.6	250 (9.84)	7.6 (.3)	65 (2.56)	65 (143)
KCTRH300-7.6	292 (11.5)	7.6 (.3)	76 (3)	65 (143)
KCTRH370-7.6	368 (14.49)	7.6 (.3)	102 (4.02)	65 (143)
KCTRH430-7.6	430 (16.93)	7.6 (.3)	110 (4.33)	65 (143)
KCTRH530-7.6	533 (21)	7.6 (.3)	140 (5.51)	65 (143)

These ties have a round-shaped head which provides greater strength for a given tie width.

## HEAVY DUTY TIES - TIE WIDTH 13mm



PART NO.	LENGTH mm (inches)	WIDTH mm (inches)	MAX. BUNDLE DIAMETER mm (inches)	MIN. TENSILE STRENGTH Kg (lbs)
KCT230-13	230 (9.06)	13 (.51)	50 (1.97)	114 (250)
KCT480-13	480 (18.9)	13 (.51)	120 (4.72)	114 (250)
KCT580-13	580 (22.83)	13 (.51)	152 (6)	114 (250)
KCT730-13	730 (28.74)	13 (.51)	204 (8.03)	114 (250)
KCT1030-13	1030 (40.55)	13 (.51)	295 (11.61)	114 (250)

For applications where very high strength is required, Kompress Heavy Duty ties should be specified.


## LASHING TIES - TIE WIDTH 13mm



PART NO.	LENGTH mm (inches)	WIDTH mm (inches)	MAX. BUNDLE DIAMETER mm (inches)	MIN. TENSILE STRENGTH Kg (lbs)
KCTLT240-13	240 (9.45)	13 (.51)	50 (1.97)	114 (250)
KCTLT490-13	490 (19.29)	13 (.51)	120 (4.72)	114 (250)
KCTLT590-13	590 (23.23)	13 (.51)	152 (6)	114 (250)
KCTLT740-13	740 (29.13)	13 (.51)	204 (8.03)	114 (250)
KCTLT890-13	890 (35.04)	13 (.51)	248 (9.76)	114 (250)
KCTLT1040-13	1040 (40.94)	13 (.51)	295 (11.61)	114 (250)

Kompress Lashing Ties have the same strength as Heavy Duty Ties and their double fastening system allows a neat finish when cutting off the end of the tail is not possible.


## FLAT HEAD NYLON 11/12 TIES



PART NO.	LENGTH mm (inches)	WIDTH mm (inches)	THICK mm (inches)	MAX. BUNDLE DIAMETER mm (inches)	MIN. TENSILE STRENGTH Kg (lbs)
KCTFH180-8.6	180 (7.09)	8.6 (.34)	2.0 (.08)	40 (1.57)	15.6 (35)
KCTFH260-8.6	180 (7.09)	8.6 (.34)	2.0 (.08)	53 (2.09)	22.2 (50)
KCTFH360-8.6	180 (7.09)	8.6 (.34)	2.0 (.08)	83 (3.27)	22.2 (50)

Made from non-hydroscopic Nylon 11/12 material, these ties have a flat fastening angle to provide a neat finish.

## RELEASABLE CABLE TIES



PART NO.	LENGTH mm (inches)	WIDTH mm (inches)	MAX. BUNDLE DIAMETER mm (inches)	MIN. TENSILE STRENGTH Kg (lbs)
KRCT140-3.6	140 (5.51)	3.6 (.14)	33 (1.3)	13.7 (30)
KRCT200-4.8	200 (7.87)	4.8 (.19)	50 (1.97)	22.2 (50)
KRCT300-4.8	300 (11.81)	4.8 (.19)	76 (3)	22.2 (50)
KRCT370-4.8	370 (14.57)	4.8 (.19)	102 (4.02)	22.2 (50)
KRCT100-7.6	100 (3.94)	7.6 (.3)	20 (.79)	22.2 (50)
KRCT120-7.6	120 (4.72)	7.6 (.3)	30 (1.18)	22.2 (50)
KRCT150-7.6	150 (5.91)	7.6 (.3)	35 (1.38)	22.2 (50)
KRCT200-7.6	200 (7.87)	7.6 (.3)	50 (1.97)	22.2 (50)
KRCT250-7.6	250 (9.84)	7.6 (.3)	66 (2.6)	22.2 (50)
KRCT300-7.6	300 (11.81)	7.6 (.3)	80 (3.15)	22.2 (50)
KRCT370-7.6	370 (14.57)	7.6 (.3)	120 (4.72)	22.2 (50)

## PANEL MOUNTING TIES




PART NO.	LENGTH mm (inches)	WIDTH mm (inches)	MAX. BUNDLE DIAMETER mm (inches)	MIN. TENSILE STRENGTH Kg (lbs)	HOLE DIAMETER mm (inches)	MAX. PANEL THICKNESS mm (inches)
KCTPM155-3.5	150 (5.9)	3.5 (.14)	32 (1.26)	13.7 (30)	5.2 (.2)	2.8 (.11)
KCTPM200-4.6	200 (7.87)	4.6 (.18)	46 (1.81)	22.2 (50)	6.3 (.25)	3.6 (.14)

## LOCKING PANEL MOUNTING TIES




PART NO.	LENGTH mm (inches)	WIDTH mm (inches)	MAX. BUNDLE DIAMETER mm (inches)	MIN. TENSILE STRENGTH Kg (lbs)	HOLE DIAMETER mm (inches)	MAX. PANEL THICKNESS mm (inches)
KCTLPM110-2.5	110 (4.3)	2.5 (0.1)	22 (.87)	8.1 (18)	4.8 (0.19)	2.0 (0.08)
KCTLPM130-3.2	130 (5.1)	3.2 (0.13)	28 (1.10)	13.6 (30)	4.0 (0.16)	2.4 (0.09)
KCTLPM130-4.8	130 (5.1)	4.8 (0.19)	25 (.98)	22.2 (50)	6.4 (0.25)	3.2 (0.13)
KCTLPM170-4.8	170 (6.7)	4.8 (0.19)	38 (1.5)	22.2 (50)	6.4 (0.25)	3.2 (0.13)
KCTLPM195-4.8	195 (7.7)	4.8 (0.19)	45 (1.77)	22.2 (50)	6.4 (0.25)	3.2 (0.13)

## MOUNTING HEAD TIES




PART NO.	LENGTH mm (inches)	WIDTH mm (inches)	MAX. BUNDLE DIA. mm (inches)	MIN. TENSILE STRENGTH Kg (lbs)
KCTMH110-2.5	110 (4.33)	2.5 (.1)	22 (.87)	8.1 (18)
KCTMH150-3.6	150 (5.91)	3.6 (.14)	32 (1.26)	18.2 (40)
KCTMH200-4.8	200 (7.87)	4.8 (.19)	50 (1.97)	22.2 (50)
KCTMH300-4.8	319 (12.56)	4.8 (.19)	76 (3)	22.2 (50)
KCTMH200-7.6	200 (7.87)	7.6 (.3)	50 (1.97)	54.4 (120)
KCTMH300-7.6	305 (12)	7.6 (.3)	76 (3)	54.4 (120)
KCTMH380-7.6	380 (14.96)	7.6 (.3)	102 (4.02)	54.4 (120)


## MARKER TIES - (AREA 20x9)

	PART NO.	LENGTH	WIDTH	MAX. BUNDLE DIAMETER	MIN. TENSILE STRENGTH	MARKING AREA
		mm (inches)	mm (inches)	mm (inches)	Kg (lbs)	mm (inches)
	KCTMFT110-2.5	110 (4.4)	2.5 (.1)	18 (.71)	8.1 (18)	20.4x9.1 (.8x.36)
	KCTMFT200-2.5	210 (8.27)	2.5 (.1)	50 (1.97)	8.1 (18)	20.4x9.1 (.8x.36)


## MARKER TIES - (AREA 25x8)

	PART NO.	LENGTH	WIDTH	MAX. BUNDLE DIAMETER	MIN. TENSILE STRENGTH	MARKING AREA
		mm (inches)	mm (inches)	mm (inches)	Kg (lbs)	mm (inches)
	KCTMT150-3.6	100 (3.94)	2.5 (.1)	18 (.71)	8.1 (18)	25.4x8 (1x.31)
	KCTMT200-4.8	200 (7.87)	2.5 (.1)	50 (1.97)	8.1 (18)	25.4x8 (1x.31)


## MARKER TIES - (AREA 13x28)

	PART NO.	LENGTH	WIDTH	MAX. BUNDLE DIAMETER	MIN. TENSILE STRENGTH	MARKING AREA
		mm (inches)	mm (inches)	mm (inches)	Kg (lbs)	mm (inches)
	KCTMT220-4.8	220 (8.66)	4.8 (.19)	54 (2.13)	22.2 (50)	13x28 (.51x1.1)
	KCTMT300-4.8	300 (11.81)	4.8 (.19)	76 (3)	22.2 (50)	13x28 (.51x1.1)
	KCTMT370-4.8	370 (14.57)	4.8 (.19)	102 (4.02)	22.2 (50)	13x28 (.51x1.1)


## MARKER TIES - (AREA 30x28)

	PART NO.	LENGTH	WIDTH	MAX. BUNDLE DIAMETER	MIN. TENSILE STRENGTH	MARKING AREA
		mm (inches)	mm (inches)	mm (inches)	Kg (lbs)	mm (inches)
	KCTMT2-220-4.8	220 (8.66)	4.8 (.16)	54 (2.13)	22.2 (50)	30x28 (1.85x1.1)
	KCTMT2-300-4.8	300 (11.81)	4.8 (.16)	76 (3)	22.2 (50)	30x28 (1.85x1.1)
	KCTMT2-370-4.8	370 (14.57)	4.8 (.16)	102 (4.02)	22.2 (50)	30x28 (1.85x1.1)


## MARKER TIES - (AREA 47x28)

	PART NO.	LENGTH	WIDTH	MAX. BUNDLE DIAMETER	MIN. TENSILE STRENGTH	MARKING AREA
		mm (inches)	mm (inches)	mm (inches)	Kg (lbs)	mm (inches)
	KCTMT3-220-4.8	220 (8.66)	4.8 (.16)	54 (2.13)	22.2 (50)	47x28 (1.85x1.1)
	KCTMT3-300-4.8	300 (11.81)	4.8 (.16)	76 (3)	22.2 (50)	47x28 (1.85x1.1)
	KCTMT3-370-4.8	370 (14.57)	4.8 (.16)	102 (4.02)	22.2 (50)	47x28 (1.85x1.1)


## MARKER TIES - (AREA 13x55)

	PART NO.	LENGTH	WIDTH	MAX. BUNDLE DIAMETER	MIN. TENSILE STRENGTH	MARKING AREA
		mm (inches)	mm (inches)	mm (inches)	Kg (lbs)	mm (inches)
	KCTMTL220-4.8	220 (8.66)	4.8 (.16)	54 (2.13)	22.2 (50)	13x55 (.51x2.17)
	KCTMTL300-4.8	300 (11.81)	4.8 (.16)	76 (3)	22.2 (50)	13x55 (.51x2.17)
	KCTMTL370-4.8	370 (14.57)	4.8 (.16)	102 (4.02)	22.2 (50)	13x55 (.51x2.17)

## MARKER TIES - (AREA 30x55)

	PART NO.	LENGTH	WIDTH	MAX. BUNDLE DIAMETER	MIN. TENSILE STRENGTH	MARKING AREA
		mm (inches)	mm (inches)	mm (inches)	Kg (lbs)	mm (inches)
	KCTMTL2-220-4.8	220 (8.66)	4.8 (.16)	54 (2.13)	22.2 (50)	29.8x55 (1.17x2.17)
	KCTMTL2-300-4.8	300 (11.81)	4.8 (.16)	76 (3)	22.2 (50)	29.8x55 (1.17x2.17)
	KCTMTL2-370-4.8	370 (14.57)	4.8 (.16)	102 (4.02)	22.2 (50)	29.8x55 (1.17x2.17)

## MARKER TIES - (AREA 47x55)

	PART NO.	LENGTH	WIDTH	MAX. BUNDLE DIAMETER	MIN. TENSILE STRENGTH	MARKING AREA
		mm (inches)	mm (inches)	mm (inches)	Kg (lbs)	mm (inches)
	KCTMTL3-220-4.8	220 (8.66)	4.8 (.16)	54 (2.13)	22.2 (50)	47x55 (1.85x2.17)
	KCTMTL3-300-4.8	300 (11.81)	4.8 (.16)	76 (3)	22.2 (50)	47x55 (1.85x2.17)
	KCTMTL3-370-4.8	370 (14.57)	4.8 (.16)	102 (4.02)	22.2 (50)	47x55 (1.85x2.17)

## SELF ADHESIVE MOUNTS



PART NO.	BASE WIDTH mm (inches)	BASE LENGTH mm (inches)	HEIGHT mm (inches)	MAX. TIE WIDTH mm (inches)	SCREW SIZE metric (US)
KCTMSA-20X2	20 (.79)	20 (.79)	5 (.2)	5 (.2)	-
KCTMSA-28X2	25 (.98)	25 (.98)	7 (.28)	5 (.2)	M5 (#10)
KCTMSA-30X2	28 (1.1)	28 (1.1)	7 (.28)	5 (.2)	M6 (¼)

4-Way nylon mounts for rapid fixing to smooth, dry, clean surfaces.  
Supplied in pairs for ease of use. KCTMSA-28 and KCTMSA-30 can also be fixed with screws.  
**Colours:** Natural and Black (add suffix BL)

## SCREW FIXING MOUNTS




PART NO.	WIDTH mm (inches)	LENGTH mm (inches)	HEIGHT mm (inches)	MAX. TIE WIDTH mm (inches)	SCREW SIZE metric (US)
KCTSM2	9.5 (.37)	14.9 (.59)	6.9 (.27)	4.8 (.19)	M4 (#8)
KCTSM3M5	15.5 (.61)	23.5 (.93)	9.2 (.36)	7.6 (.3)	M5 (#10)
KCTSM3M6S	15.5 (.61)	23.5 (.93)	9.2 (.36)	7.6 (.3)	M6 (¼)
KCTSM3M6L	15.5 (.61)	23.5 (.93)	9.2 (.36)	7.6 (.3)	M6 (¼)

## LOW-PROFILE MOUNTS



PART NO.	WIDTH mm (inches)	LENGTH mm (inches)	HEIGHT mm (inches)	MAX. TIE WIDTH mm (inches)	SCREW SIZE metric (US)
KCTSMPL1	8.1 (.32)	10.2 (.4)	2.5 (.1)	2.5 (.1)	M3 (#5)
KCTSMPL2	12.7 (.5)	19.1 (.75)	3.0 (.12)	4.8 (.19)	M4 (#8)

## KNOCK-IN LOW-PROFILE MOUNTS



PART NO.	WIDTH mm (inches)	LENGTH mm (inches)	HEIGHT mm (inches)	MAX. TIE WIDTH mm (inches)	RECOMM. HOLE DIA. mm (inches)
KCTKMLP3	12.6 (.5)	19 (.75)	3.0 (.12)	4.8 (.19)	3.6 (.14)
KCTKMLP4	12.6 (.5)	19 (.75)	3.0 (.12)	4.8 (.19)	4.3 (.17)
KCTKMLP5	12.6 (.5)	19 (.75)	3.0 (.12)	4.8 (.19)	5.0 (.2)

## MASONRY MOUNTS



PART NO.	RECOMM. HOLE DIA. mm (inches)	MOUNT LENGTH mm (inches)	MAX. TIE WIDTH mm (inches)
KCTMM1	7 (.28)	38.5 (1.51)	9 (.35)
KCTMM2	6 (.24)	37.4 (1.47)	9 (.35)

For fixing cables to walls without using screws or plugs.  
**Colours and Material:** Black Nylon

## VERTICAL FLANGE MOUNTS



PART NO.	FLANGE THICKNESS RANGE mm (inches)
KCTFMV-5	1.5-5 (.06-.2)
KCTFMV-7	5-7 (.2-.28)

Hammer onto vertical steelwork flanges to provide secure fixing for cables, pipes, tubing etc.  
**Flange Grip:** Painted Steel - Plated Steel also available (add suffix PL)  
**Mount:** Natural Nylon. Maximum cable tie width 7.6mm, supplied separately.

## HORIZONTAL FLANGE MOUNTS



PART NO.	FLANGE THICKNESS RANGE
	mm (inches)
KCTFMH-7	3-8 (.12-.31)
KCTFMH-13	8-14 (.31-.55)
KCTFMH-20	14-20 (.55-.79)

Hammer onto horizontal steelwork flanges to provide secure fixing for cables, pipes, tubing etc.  
**Flange Grip:** Black Painted Steel - Plated Steel also available (add suffix PL)  
**Mount:** Natural Nylon. Maximum cable tie width 7.6mm (.3 inches), supplied separately.

## SELF ADHESIVE CABLE CLIPS



PART NO.	MAX. BUNDLE DIAMETER	BASE WIDTH	BASE LENGTH	HEIGHT
	mm (inches)	mm (inches)	mm (inches)	mm (inches)
KCCSA-20	4.8 (.19)	19.0 (.75)	15.9 (.63)	7.4 (.29)
KCCSA-25	9.6 (.38)	25.4 (1)	25.4 (1)	11.7 (.46)
KCCSA-30	15.7 (.62)	28.6 (1.13)	31.7 (1.25)	17.1 (.67)

For rapid fixing to smooth, dry clean surfaces.

**Colour and Material:** Natural Nylon.

## SELF ADHESIVE LOCKING CLIPS



PART NO.	MAX. BUNDLE DIAMETER	BASE WIDTH	BASE LENGTH	HEIGHT
	mm (inches)	mm (inches)	mm (inches)	mm (inches)
KALC-5	5.3 (.21)	13.1 (.52)	24.4 (.96)	10.1 (.4)
KALC-9	9.2 (.36)	15.6 (.61)	21.8 (.86)	13.9 (.55)
KALC-14	13.5 (.53)	18.2 (.72)	28.7 (1.13)	18.7 (.74)
KALC-20	20.0 (.79)	24.7 (.97)	33.3 (1.31)	25.0 (.98)

Locking feature securely holds cable bundle and can easily be unlocked for repair and maintenance work

**Colour and Material:** Grey Nylon.

## NYLON CLIPS



PART NO.	MAX. BUNDLE DIAMETER	WIDTH	LENGTH	SCREW SIZE
	mm (inches)	mm (inches)	mm (inches)	metric (US)
KNC3.2	3.2 (.13)	9.6 (.38)	19.8 (.78)	M4 (#8)
KNC4.8	4.8 (.19)	9.6 (.38)	19.8 (.78)	M4 (#8)
KNC6.7	6.7 (.26)	10.0 (.39)	22.0 (.87)	M4 (#8)
KNC7.9	7.9 (.31)	10.0 (.39)	22.0 (.87)	M4 (#8)
KNC9.5	9.5 (.37)	12.0 (.47)	24.0 (.94)	M4 (#8)
KNC12.7	12.7 (.5)	12.0 (.47)	31.0 (1.22)	M4 (#8)
KNC15.8	15.8 (.62)	12.0 (.47)	34.3 (1.35)	M5 (#10)
KNC19.4	19.4 (.76)	12.0 (.47)	35.0 (1.38)	M5 (#10)
KNC25.4	25.4 (1)	12.0 (.47)	43.0 (1.69)	M5 (#10)
KNC31.8	31.8 (1.25)	12.0 (.47)	46.2 (1.82)	M5 (#10)
KNC36.7	36.7 (1.44)	12.0 (.47)	50.0 (1.97)	M5 (#10)

**Colour and Material:** Natural Nylon.

## SELF ADHESIVE FLAT CABLE CLIPS



PART NO.	LENGTH	WIDTH	HEIGHT
	mm (inches)	mm (inches)	mm (inches)
KSAFCC15	15 (.59)	25 (.98)	6 (.24)
KSAFCC28	28 (1.1)	25 (.98)	6 (.24)

**Colour and Material:** Grey PVC.



## VELCRO TIES

	PART NO.	LENGTH	WIDTH	MAX. BUNDLE DIAMETER
		mm (inches)	mm (inches)	mm (inches)
	KCT200-12V BLACK	200 (7.87)	12 (.47)	50 (2.36)
	KCT200-12V WHITE	200 (7.87)	12 (.47)	50 (2.36)
	KCT200-12V RED	200 (7.87)	12 (.47)	50 (2.36)
	KCT200-12V GREEN	200 (7.87)	12 (.47)	50 (2.36)
	KCT200-12V BLUE	200 (7.87)	12 (.47)	50 (2.36)
	KCT200-12V YELLOW	200 (7.87)	12 (.47)	50 (2.36)
	KCT300-16V BLACK	300 (11.81)	16 (.63)	75 (2.95)
	KCT300-16V WHITE	300 (11.81)	16 (.63)	75 (2.95)
	KCT300-16V RED	300 (11.81)	16 (.63)	75 (2.95)
	KCT300-16V GREEN	300 (11.81)	16 (.63)	75 (2.95)
	KCT300-16V BLUE	300 (11.81)	16 (.63)	75 (2.95)
	KCT300-16V YELLOW	300 (11.81)	16 (.63)	75 (2.95)

For use with delicate cables or in applications where the ability to re-use or adjust easily is beneficial.

## SPIRAL WRAPPING BAND

	PART NO.	BUNDLE DIAMETER RANGE	INSIDE DIAMETER	WALL THICKNESS	WIDTH
		mm (inches)	mm (inches)	mm (inches)	mm (inches)
	KSW5-50	5-50 (.2-1.97)	4 (.16)	1.0 (0.04)	7.0 (.28)
	KSW10-65	10-65 (.39-2.56)	6 (.24)	1.25 (0.05)	11.4 (.45)
	KSW15-80	15-80 (.59-3.15)	12 (.47)	1.5 (0.06)	15.0 (.59)
	KSW25-130	25-130 (.98-5.12)	20 (.79)	2.0 (0.08)	19.6 (.77)

Operating temperature: -60°C to 70°C  
Colour and Material: Natural and black Polyethylene

## CABLE TIE TENSIONING TOOLS

	PART NO.	DESCRIPTION
		KCTIT2

## CABLE TIE TENSIONING TOOLS

	PART NO.	DESCRIPTION
		KCTIT3

## CABLE TIE TENSIONING TOOLS

	PART NO.	DESCRIPTION
		KCTIT5



KOMPRESS HOLDINGS LTD  
LITTLE TENNIS STREET  
NOTTINGHAM NG2 4EL  
UNITED KINGDOM  
TEL: +44 (0) 115 958 1029  
FAX: +44 (0) 115 958 4180

KOMPRESS, INC.  
820 NE 24TH LANE, WH # 105  
CAPE CORAL, FL 33909  
USA  
TEL: +1 941-573-8780  
FAX: +1 941-573-8779

KOMPRESS GMBH  
MARSTRABE 7B  
44579 CASTROP RAUXEL  
GERMANY  
TEL +49 (0) 2305 18511/18051  
FAX: +49 (0) 49 2305 33331

E-mail: [sales@kompres.com](mailto:sales@kompres.com)  
Website: [www.kompres.com](http://www.kompres.com)