



Earth Rod to Tape 'A' Clamps

These clamps are used for joining earth rods to different sizes of copper tape. The clamps have a high resistance to corrosion and are mechanically strong to ensure a lasting connection.

Earth Rod Shank Ø mm	Maximum Tape Size mm	L mm	W mm	H mm	Unit Weight kg	Pack Quantity	Part Number
12.7	26 x 15	43	36	19	0.12	50	ERA 1625
	32 x 15	42	44	18	0.13	25	ERA 1631
	39 x 15	46	52	23	0.20	25	ERA 1638
14.2	26 x 14	43	36	19	0.12	50	ERA 1625
	32 x 14	42	44	18	0.13	25	ERA 1631
	39 x 14	46	52	23	0.20	25	ERA 1638
	51 x 16	48	63	20	0.20	25	ERA 1650
15.0	26 x 13	43	36	19	0.12	50	ERA 1625
	32 x 13	42	44	18	0.13	25	ERA 1631
	39 x 13	46	52	23	0.20	25	ERA 1638
	51 x 15	48	63	20	0.20	25	ERA 1650
16.0	26 x 12	43	36	19	0.12	50	ERA 1625
	32 x 12	42	44	18	0.13	25	ERA 1631
	39 x 12	46	52	23	0.20	25	ERA 1638
	51 x 14	48	63	20	0.20	25	ERA 1650
17.2	26 x 11	43	36	19	0.12	50	ERA 1625
	32 x 11	42	44	18	0.13	25	ERA 1631
	39 x 11	46	52	23	0.20	25	ERA 1638
	51 x 13	48	63	20	0.20	25	ERA 1650
	26 x 18	54	38	22	0.17	10	ERA 2525
20.0	26 x 8	43	36	19	0.12	50	ERA 1625
	32 x 8	42	44	18	0.13	25	ERA 1631
	39 x 8	46	52	23	0.20	25	ERA 1638
	51 x 10	48	63	20	0.20	25	ERA 1650
	26 x 16	54	38	22	0.17	10	ERA 2525
25.0	26 x 11	54	38	22	0.17	10	ERA 2525

Material: Aluminium Bronze with M10 x 25mm Phosphor Bronze Set Screw.

*The ERA 1625 comes with a Stainless Steel Grade 316 Set Screw.

The aluminium version is mainly used for connecting aluminium tape to a puddle flange rod as part of a lightning protection system.

Earth Rod Shank Ø mm	Maximum Tape Size mm	L mm	W mm	H mm	Unit Weight kg	Pack Quantity	Part Number
16.0	26 x 12	45	37	19	0.06	25	ERA 1625A

Material: Aluminium with M10 x 25mm Stainless Steel Set Screw.



BS EN 62561-1 Class H



Tightening Torque 20 Nm

