

ERU 025

### 'U' Bolt Clamps


This versatile range of Wallis 'U' bolt clamps can be used to connect flat tapes and stranded cables to earth rods, reinforcing bars (rebar), hand rails etc.

### Single Plate Type for Horizontal Flat Tapes

Used to connect flat tapes in a horizontal position on the rod.

Maximum Rod Ø mm	Hole Centres mm	L mm	W mm	H mm	Unit Weight kg	Pack Quantity	Part Number
16	30	58	62	33	0.17	20	ERU 016
25	37	72	62	33	0.19	20	ERU 025
31	41	82	68	33	0.25	10	ERU 031
38	46	90	75	33	0.29	10	ERU 038
50	63	95	90	33	0.39	5	ERU 050

**Material:** High Copper Alloy plate with M10 threaded Copper 'U' Bolt.




ERU 216

### Double Plate Type for Vertical Flat Tapes

Used to connect flat tapes in a vertical position on the rod.

Maximum Rod Ø mm	Tape Width mm	L mm	W mm	H mm	Unit Weight kg	Pack Quantity	Part Number
16	25	58	62	33	0.23	20	ERU 216
25		73	60	33	0.23	10	ERU 225
31		85	68	33	0.32	10	ERU 231
38		80	75	33	0.34	10	ERU 238
50		103	90	33	0.53	5	ERU 250

**Material:** High Copper Alloy plates with M10 threaded Copper 'U' Bolt.



ERU 470

### Double Plate Type for Vertical Stranded Cables

Used to connect stranded cables in a vertical and horizontal position on the rod.

Maximum Rod Ø mm	Conductor Range mm <sup>2</sup>	L mm	W mm	H mm	Unit Weight kg	Pack Quantity	Part Number
16	16 - 150	57	52	40	0.21	20	ERU 470
	150 - 300	69	70		0.30	10	ERU 570
20	16 - 70	57	52	40	0.21	20	ERU 470
	70 - 300	69	70		0.30	10	ERU 570
25	16 - 70	75	87	55	0.52	5	ERU 670
	185 - 300	89	70		0.46	7	ERU 770

**Material:** High Copper Alloy plates with M10 threaded Copper 'U' Bolt.  
The ERU470 has an M8 threaded Copper 'U' bolt.



BS EN 62561-1 Class H



Tightening torque 20 Nm; ERU470 13 Nm; ERU770 12 Nm

