

Split Connector Clamps

Split connector clamps are used to connect cable lugs onto earth rods. The clamps are designed to suit our full range of earth rods. All clamps are assembled with an M12 x 50mm set screw and fittings, except ERS010 which has an M8 x 40mm set screw and fittings. ERC24 also has a wing nut.

For use with Copperbond Earth Rods (on rod thread)

| Nominal Rod Size | Thread Size (UNC-2A) | L mm | W mm | H mm | Unit Weight kg | Pack Quantity | Part Number |
|------------------|----------------------|------|------|------|----------------|---------------|-------------|
| 5/8" | 5/8" | 42 | 24 | 26 | 0.21 | 10 | ERS 016 |
| 3/4" | 3/4" | 51 | 31 | 30 | 0.34 | | ERS 020 |

Material: High Copper Alloy.

For use with Copperbond Earth Rods (on rod shank)

| Rod Shank Ø mm | L mm | W mm | H mm | Unit Weight kg | Pack Quantity | Part Number |
|----------------|------|------|------|----------------|---------------|-------------|
| 9.5 | 26 | 16 | 20 | 0.07 | 10 | ERS 010 |
| 14.2 | 42 | 25 | 25 | 0.26 | | ERC 24 |

Material: High Copper Alloy.

For use with Solid Copper & Stainless Steel Earth Rods (on rod shank)

| Rod Shank Ø mm | L mm | W mm | H mm | Unit Weight kg | Pack Quantity | Part Number |
|----------------|------|------|------|----------------|---------------|-------------|
| 15 | 42 | 26 | 25 | 0.21 | 10 | ERC 26 |
| 16 | 42 | 25 | 26 | 0.21 | | ERSS 16 |
| 20 | 54 | 29 | 29 | 0.23 | | ERSS 20 |

Material: High Copper Alloy.



BS EN 62561-1 Class H

ERS 016



ERC 24



ERSS 20

